



## Safety Data Sheet

### Section 1: Identification

#### Product identifier

- Product Name** • **Carbon Dioxide (Refrigerated Liquid)**
- Synonyms** • Carbonic anhydride
- CAS Number** • 124-38-9
- Product Code** • MSDS No.: 90059

#### Relevant identified uses of the substance or mixture and uses advised against

- Recommended use** • Carbonation, chilling or freezing operations, and other.

#### Details of the supplier of the safety data sheet

- Manufacturer** • Air Liquide  
9811 Katy Freeway, Suite 100  
Houston, TX 77024  
United States  
www.us.airliquide.com .

**Telephone (Technical)** • 713-896-2896

**Telephone (Technical)** • 800-819-1704

#### Emergency telephone number

- Manufacturer** • 800-424-9300 - CHEMTREC
- Manufacturer** • +1 703-527-3887 - Outside United States

### Section 2: Hazard Identification

#### United States (US)

According to OSHA 29 CFR 1910.1200 HCS

#### Classification of the substance or mixture

- OSHA HCS 2012** • Refrigerated Liquefied Gas - H281  
Simple Asphyxiant  
Hazards Not Otherwise Classified - Health Hazard - Frostbite

#### Label elements

**OSHA HCS 2012**

#### WARNING



**Hazard statements** • Contains refrigerated gas; may cause cryogenic burns or injury - H281

May displace oxygen and cause rapid suffocation.

### Precautionary statements

**Prevention** • Wear cold insulating gloves, face shield and/or eye protection. - P282

**Response** • Get immediate medical advice/attention. - P315  
Thaw frosted parts with lukewarm water. Do not rub affected area. - P336

**Storage/Disposal** • Store in a well-ventilated place. - P403

**HCS 2012 Other Information** • Mixtures containing carbon dioxide can increase respiration and heart rate.

### Other hazards

#### OSHA HCS 2012

- Contact with gas or liquefied gas will cause burns, severe injury and/or frostbite. Inhalation of carbon dioxide can increase respiration and heart rate. Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

### Canada

According to WHMIS

### Classification of the substance or mixture

#### WHMIS

- Compressed Gas - A

### Label elements

#### WHMIS



- Compressed Gas - A

### Other hazards

#### WHMIS

- Contact with gas or liquefied gas will cause burns, severe injury and/or frostbite. This material is a simple asphyxiant. May displace or reduce oxygen available for breathing especially in confined spaces. In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

### Other information

- Mixtures containing carbon dioxide can increase respiration and heart rate.

## Section 3 - Composition/Information on Ingredients

### Substances

Hazardous Components					
Chemical Name	Identifiers	%(weight)	LD50/LC50	Classifications According to Regulation/Directive	Comments
Carbon dioxide	CAS:124-38-9	> 99%	Inhalation-Rat LC50 • 470000 ppm 30 Minute(s)	OSHA HCS 2012: Simp. Asphyx.; Press. Gas - Refr. Liq.;	NDA

### Mixtures

- Material does not meet the criteria of a mixture.

See Section 11 for Toxicological Information.

## Section 4: First-Aid Measures

### Description of first aid measures

- Inhalation**
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. If signs/symptoms continue, get medical attention.
- Skin**
- If frostbite has occurred, seek medical attention immediately; do NOT rub the affected area(s) or flush them with water. In order to prevent further tissue damage, do NOT attempt to remove frozen clothing from frostbitten areas. If frostbite has not occurred, immediately and thoroughly wash contaminated skin with soap and water.
- Eye**
- If eye tissue is frozen, seek medical attention immediately; if tissue is not frozen, immediately and thoroughly flush the eyes with large amounts of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. If irritation, pain, swelling, lacrimation or photophobia persist, get medical attention as soon as possible.
- Ingestion**
- If frostbite has occurred, seek medical attention immediately; do NOT rub the affected area(s) or flush them with water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting.

### Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

### Indication of any immediate medical attention and special treatment needed

- Notes to Physician**
- All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

### Other information

- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. RESCUERS SHOULD NOT ATTEMPT TO RETRIEVE VICTIMS OF EXPOSURE TO GASES WITHOUT ADEQUATE PERSONAL PROTECTIVE EQUIPMENT. At a minimum, Self-Contained Breathing Apparatus must be worn. Victim(s) who experience any adverse effect after over-exposure to this gas mixture must be taken for medical attention. Rescuers should be taken for medical attention if necessary. Take a copy of the label and the MSDS to physician or other health professional with victim(s).

## Section 5: Fire-Fighting Measures

### Extinguishing media

- Suitable Extinguishing Media**
- Use extinguishing agent suitable for type of surrounding fire.  
SMALL FIRES: Dry chemical or CO<sub>2</sub>.  
LARGE FIRES: Water spray or fog.
- Unsuitable Extinguishing Media**
- No data available

### Special hazards arising from the substance or mixture

- Unusual Fire and Explosion Hazards**
- Containers may explode when heated.  
Ruptured cylinders may rocket.
- Hazardous Combustion Products**
- No data available

### Advice for firefighters

- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.  
Always wear thermal protective clothing when handling refrigerated/cryogenic liquids. Wear positive pressure self-contained breathing apparatus (SCBA).  
Move containers from fire area if you can do it without risk.  
FIRE: If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.  
FIRE INVOLVING TANKS: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.  
FIRE INVOLVING TANKS: Cool containers with flooding quantities of water until well after fire is out.  
FIRE INVOLVING TANKS: Do not direct water at source of leak or safety devices; icing may occur.  
FIRE INVOLVING TANKS: Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.  
FIRE INVOLVING TANKS: ALWAYS stay away from tanks engulfed in fire.

## Section 6 - Accidental Release Measures

### Personal precautions, protective equipment and emergency procedures

#### Personal Precautions

- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material. Ventilate the area before entry.

#### Emergency Procedures

- Stop leak if you can do it without risk. Keep unauthorized personnel away. Keep out of low areas. Stay upwind. Do not direct water at spill or source of leak. LARGE SPILL: Consider initial downwind evacuation for at least 500 meters (1/3 mile)

### Environmental precautions

- No special environmental precautions necessary.

### Methods and material for containment and cleaning up

#### Containment/Clean-up Measures

- Stop leak if you can do it without risk.  
Do not direct water at spill or source of leak.  
Use water spray to reduce vapors; do not put water directly on leak, spill area or inside container.  
If possible, turn leaking containers so that gas escapes rather than liquid.  
Isolate area until gas has dispersed.  
Ventilate the area.  
Allow substance to evaporate.

## Section 7 - Handling and Storage

### Precautions for safe handling

#### Handling

- Use only with adequate ventilation. Ventilate closed spaces before entering. Be aware of any signs of dizziness or fatigue, especially if work is done in a poorly ventilated area; exposures to fatal concentrations of this gas mixture could occur without any significant warning symptoms, due to olfactory fatigue or oxygen deficiency. Cylinders should be firmly secured to prevent falling or being knocked-over. Do not attempt to repair, adjust, or in any other way modify cylinders. If there is a malfunction or another type of operational problem, contact nearest distributor immediately. Empty containers retain product residue and can be hazardous. Do not cut, weld, puncture or incinerate container.

### Conditions for safe storage, including any incompatibilities

#### Storage

- Store in a cool, dry, well-ventilated place. Protect cylinders against physical damage. Cylinders should be firmly secured to prevent falling or being knocked-over.

## Section 8 - Exposure Controls/Personal Protection

### Control parameters

Exposure Limits/Guidelines						
	Result	ACGIH	Canada Ontario	Canada Quebec	NIOSH	OSHA
Carbon dioxide (124-38-9)	STELs	30000 ppm STEL	30000 ppm STEL	30000 ppm STEV; 54000 mg/m3 STEV	30000 ppm STEL; 54000 mg/m3 STEL	Not established
	TWAs	5000 ppm TWA	5000 ppm TWA	5000 ppm TWAEV; 9000 mg/m3 TWAEV	5000 ppm TWA; 9000 mg/m3 TWA	5000 ppm TWA; 9000 mg/m3 TWA

### Exposure controls

#### Engineering Measures/Controls

- Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof - electrical, ventilating and/or lighting equipment.

#### Personal Protective Equipment

##### Respiratory

- In case of insufficient ventilation, wear suitable respiratory equipment.

##### Eye/Face

- Wear safety glasses.

##### Skin/Body

- Wear leather gloves when handling cylinders.

#### Environmental Exposure Controls

- Follow best practice for site management and disposal of waste. Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways.

#### Key to abbreviations

STEL = Short Term Exposure Limits are based on 15-minute exposures

STEV = Short Term Exposure Value

TWAEV = Time-Weighted Average Exposure Value

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

ACGIH = American Conference of Governmental Industrial Hygiene

NIOSH = National Institute of Occupational Safety and Health

OSHA = Occupational Safety and Health Administration

## Section 9 - Physical and Chemical Properties

### Information on Physical and Chemical Properties

Material Description			
Physical Form	Gas	Appearance/Description	Colorless, odorless, nonflammable compressed liquified gas.
Color	Colorless	Odor	Odorless
Taste	Data lacking	Particulate Type	Not relevant
Particulate Size	Not relevant	Aerosol Type	Not relevant
Odor Threshold	Not relevant	Physical and Chemical Properties	Data lacking
General Properties			
Boiling Point	Data lacking	Melting Point	Data lacking
Decomposition Temperature	Data lacking	Heat of Decomposition	Data lacking
pH	Data lacking	Specific Gravity/Relative Density	Data lacking
Density	Data lacking	Bulk Density	Data lacking
Water Solubility	Data lacking	Solvent Solubility	Data lacking
Viscosity	Data lacking	Explosive Properties	Not explosive.
Oxidizing Properties:	Not an oxidizer.		

**Volatility**

Vapor Pressure	Data lacking	Vapor Density	Data lacking
Evaporation Rate	Data lacking	VOC (Wt.)	Data lacking
VOC (Vol.)	Data lacking	Volatiles (Wt.)	Data lacking
Volatiles (Vol.)	Data lacking		

**Flammability**

Flash Point	Not relevant	UEL	Not relevant
LEL	Not relevant	Autoignition	Not relevant
Self-Accelerating Decomposition Temperature (SADT)	Not relevant	Heat of Combustion ( $\Delta H_c$ )	Not relevant
Burning Time	Not relevant	Flame Height	Not relevant
Flame Extension	Not relevant	Ignition Distance	Not relevant
Flame Duration	Not relevant	Flammability (solid, gas)	Not flammable.

**Environmental**

Half-Life	Data lacking	Octanol/Water Partition coefficient	Data lacking
Coefficient of water/oil distribution	Data lacking	Bioaccumulation Factor	Data lacking
Bioconcentration Factor	Data lacking	Biochemical Oxygen Demand BOD/BOD5	Data lacking
Chemical Oxygen Demand	Data lacking	Persistence	Data lacking
Degradation	Data lacking		

**Section 10: Stability and Reactivity****Reactivity**

- No dangerous reaction known under conditions of normal use.

**Chemical stability**

- Stable under normal temperatures and pressures.

**Possibility of hazardous reactions**

- Hazardous polymerization will not occur.

**Conditions to avoid**

- Excess heat.

**Incompatible materials**

- This material is weakly acidic and will react with alkaline materials to form carbonates and bicarbonates.

**Hazardous decomposition products**

- Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon dioxide produces toxic carbon monoxide when heated above 1700 deg. C.

**Section 11 - Toxicological Information****Information on toxicological effects**

Carbon Dioxide (Refrigerated Liquid) 124-38-9								
Test Type	Dosage	Route	Species	Duration	Results	Test Class	Target Organs	Comments
Acute Toxicity	= 470000 ppm	Inhalation	Rat	30 Minute(s)	LC50	NDA	NDA	NDA

Reproductive	= 6 pph	Inhalation	Rat	24 Hour(s)	TCLo	NDA	NDA	NDA
GHS Properties				Classification				
Acute toxicity				OSHA HCS 2012 • Classification criteria not met				
Aspiration Hazard				OSHA HCS 2012 • Classification criteria not met				
Carcinogenicity				OSHA HCS 2012 • Classification criteria not met				
Germ Cell Mutagenicity				OSHA HCS 2012 • Classification criteria not met				
Respiratory sensitization				OSHA HCS 2012 • Classification criteria not met				
Serious eye damage/Irritation				OSHA HCS 2012 • Classification criteria not met				
Skin corrosion/Irritation				OSHA HCS 2012 • Classification criteria not met				
Skin sensitization				OSHA HCS 2012 • Classification criteria not met				
STOT-RE				OSHA HCS 2012 • Classification criteria not met				
STOT-SE				OSHA HCS 2012 • Classification criteria not met				
Toxicity for Reproduction				OSHA HCS 2012 • Classification criteria not met				

## Potential Health Effects

### Inhalation

#### Acute (Immediate)

- Inhalation of carbon dioxide can increase respiration and heart rate. If this material is released in a small, poorly ventilated area (i.e. an enclosed or confined space), an oxygen-deficient environment may occur. Individuals breathing such an atmosphere may experience symptoms which include headaches, ringing in ears, dizziness, drowsiness, unconsciousness, nausea, vomiting, and depression of all the senses. Under some circumstances of over-exposure, death may occur. The following effects associated with decreased levels of oxygen: increase in breathing and pulse rate, emotional upset, abnormal fatigue, nausea, vomiting, collapse, loss of consciousness, convulsive movements, respiratory collapse and death.

#### Chronic (Delayed)

- Under normal conditions of use, no health effects are expected.

### Skin

#### Acute (Immediate)

- Contact with gas or liquefied gas will cause burns, severe injury and/or frostbite.

#### Chronic (Delayed)

- Under normal conditions of use, no health effects are expected.

### Eye

#### Acute (Immediate)

- Contact with gas or liquefied gas will cause burns, severe injury and/or frostbite.

#### Chronic (Delayed)

- Under normal conditions of use, no health effects are expected.

### Ingestion

#### Acute (Immediate)

- Under normal conditions of use, no health effects are expected.

#### Chronic (Delayed)

- Under normal conditions of use, no health effects are expected.

### Carcinogenic Effects

- The components of this gas mixture are not found on the following lists: FEDERAL OSHA Z LIST, NTP and IARC; therefore, they are not considered to be, nor suspected to be, cancer-causing agents by these agencies.

#### Key to abbreviations

TD = Toxic Dose

LC = Lethal Concentration

## Section 12 - Ecological Information

### Toxicity

- Material data lacking.

### Persistence and degradability

- Material data lacking.

### Bioaccumulative potential

- Material data lacking.

### Mobility in Soil

- Material data lacking.

### Other adverse effects

- Material data lacking.

## Section 13 - Disposal Considerations

### Waste treatment methods

#### Product waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

#### Packaging waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

## Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	UN2187	Carbon dioxide, refrigerated liquid	2.2	NDA	NDA
TDG	UN2187	CARBON DIOXIDE, REFRIGERATED LIQUID	2.2	NDA	NDA
IMO/IMDG	UN2187	CARBON DIOXIDE, REFRIGERATED LIQUID	2.2	NDA	NDA
IATA/ICAO	UN2187	Carbon dioxide, refrigerated liquid	2.2	NDA	NDA

#### Special precautions for user

- Cylinders should be transported in a secure position, in a well-ventilated vehicle. The transportation of compressed gas cylinders in automobiles or in closed-body vehicles can present serious safety hazards. If transporting these cylinders in vehicles, ensure these cylinders are not exposed to extremely high temperatures (as may occur in an enclosed vehicle on a hot day). Additionally, the vehicle should be well-ventilated during transportation.

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

- Not relevant.

## Section 15 - Regulatory Information

### Safety, health and environmental regulations/legislation specific for the substance or mixture

**SARA Hazard Classifications** • Acute, Pressure(Sudden Release of)



State Right To Know				
Component	CAS	MA	NJ	PA
Carbon dioxide	124-38-9	Yes	Yes	Yes

Inventory						
Component	CAS	Canada DSL	Canada NDSL	China	Japan ENCS	Korea KECL
Carbon dioxide	124-38-9	Yes	No	Yes	Yes	Yes

Inventory (Con't.)		
Component	CAS	TSCA
Carbon dioxide	124-38-9	Yes

## Canada

### Labor

#### Canada - WHMIS - Classifications of Substances

- Carbon dioxide 124-38-9 > 99% A; Uncontrolled product according to WHMIS classification criteria (solid)

#### Canada - WHMIS - Ingredient Disclosure List

- Carbon dioxide 124-38-9 > 99% 1 %

### Environment

#### Canada - CEPA - Priority Substances List

- Carbon dioxide 124-38-9 > 99% Not Listed

## Mexico

### Other

#### Mexico - Hazard Classifications

- Carbon dioxide 124-38-9 > 99% Hazard Class = 2.2 UN1013; Hazard Class = 9 PG = III UN1845; Hazard Class = 2.3 UN2187

#### Mexico - Regulated Substances

- Carbon dioxide 124-38-9 > 99% UN1013; UN1845; UN2187

## United States

### Labor

#### U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals

- Carbon dioxide 124-38-9 > 99% Not Listed

**U.S. - OSHA - Specifically Regulated Chemicals**

- Carbon dioxide 124-38-9 > 99% Not Listed

**Environment**

**U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants**

- Carbon dioxide 124-38-9 > 99% Not Listed

**U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities**

- Carbon dioxide 124-38-9 > 99% Not Listed

**U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities**

- Carbon dioxide 124-38-9 > 99% Not Listed

**U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs**

- Carbon dioxide 124-38-9 > 99% Not Listed

**U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs**

- Carbon dioxide 124-38-9 > 99% Not Listed

**U.S. - CERCLA/SARA - Section 313 - Emission Reporting**

- Carbon dioxide 124-38-9 > 99% Not Listed

**U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing**

- Carbon dioxide 124-38-9 > 99% Not Listed

**United States - California**

**Environment**

**U.S. - California - Proposition 65 - Carcinogens List**

- Carbon dioxide 124-38-9 > 99% Not Listed

**U.S. - California - Proposition 65 - Developmental Toxicity**

- Carbon dioxide 124-38-9 > 99% Not Listed

**U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)**

- Carbon dioxide 124-38-9 > 99% Not Listed

**U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)**

- Carbon dioxide 124-38-9 > 99% Not Listed

**U.S. - California - Proposition 65 - Reproductive Toxicity - Female**

- Carbon dioxide 124-38-9 > 99% Not Listed

**U.S. - California - Proposition 65 - Reproductive Toxicity - Male**

- Carbon dioxide 124-38-9 > 99% Not Listed

**United States - Pennsylvania**

**Labor**

**U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List**

- Carbon dioxide 124-38-9 > 99% Not Listed

**U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances**

- Carbon dioxide 124-38-9 > 99% Not Listed

**Section 16 - Other Information**

- Last Revision Date** ● 15/January/2020  
**Preparation Date** ● 16/October/2012

**Disclaimer/Statement of Liability** ● To the best of Air Liquide's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this gas mixture is combined with other materials, all component properties must be considered. Data

may be changed from time to time. Be sure to consult the latest edition.

**Key to abbreviations**

NDA = No Data Available

---