

Safety Data Sheet



Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product identifier

- Product Name** • **Carbon Dioxide (3 - 28%), Oxygen (1 - 4%), Argon (Balance)**
- Synonyms** • Blueshield™ 22, Blueshield™ 23, Blueshield™ 24, Blueshield™ 25
- Product Code** • 10031

1.2 Relevant identified uses of the substance or mixture and uses advised against

- Relevant identified use(s)** • Welding gas mixture.

1.3 Details of the supplier of the safety data sheet

- Manufacturer** • Air Liquide
2700 Post Oak Blvd.
Houston, TX 77056
United States
www.us.airliquide.com
sds@airliquide.com
- Telephone (Technical)** • 713-896-2896
- Telephone (Technical)** • 800-819-1704

1.4 Emergency telephone number

- Manufacturer** • 800-424-9300 - CHEMTREC
- Manufacturer** • +1 703-527-3887 - Outside United States

Section 2: Hazards Identification

EU/EEC

According to EU Directive 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010]
According to EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

2.1 Classification of the substance or mixture

- CLP** • Compressed Gas - H280
- DSD/DPD** • Not classified

2.2 Label Elements

CLP

WARNING



Hazard statements • H280 - Contains gas under pressure; may explode if heated

Precautionary statements

Storage/Disposal ● P403 - Store in a well-ventilated place.

DSD/DPD

Risk phrases ● No label element(s) required

2.3 Other Hazards

CLP

- Inhalation of carbon dioxide can increase respiration and heart rate. This material is a simple asphyxiant. May displace or reduce oxygen available for breathing especially in confined spaces. According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous.

DSD/DPD

- This material is a simple asphyxiant. May displace or reduce oxygen available for breathing especially in confined spaces. Inhalation of carbon dioxide can increase respiration and heart rate. This preparation is not considered dangerous according to European Directive 1999/45/EC.
-

United States (US)

According to OSHA 29 CFR 1910.1200 HCS

2.1 Classification of the substance or mixture

- OSHA HCS 2012
- Compressed Gas - H280
Simple Asphyxiant

2.2 Label elements

OSHA HCS 2012

WARNING



- Hazard statements** ● Contains gas under pressure; may explode if heated - H280
May displace oxygen and cause rapid suffocation.

Precautionary statements

Storage/Disposal ● Store in a well-ventilated place. - P403

2.3 Other hazards

- OSHA HCS 2012
- Inhalation of carbon dioxide can increase respiration and heart rate. Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.
-

Canada

According to WHMIS

2.1 Classification of the substance or mixture

- WHMIS
- Compressed Gas - A

2.2 Label elements

WHMIS



- Compressed Gas - A


2.3 Other hazards

WHMIS

- This material is a simple asphyxiant. May displace or reduce oxygen available for breathing especially in confined spaces. Inhalation of carbon dioxide can increase respiration and heart rate. In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

2.4 Other information

- Mixtures containing carbon dioxide can increase respiration and heart rate.

**Section 3 - Composition/Information on Ingredients****3.1 Substances**

- Material does not meet the criteria of a substance in accordance with Regulation (EC) No 1272/2008.

3.2 Mixtures

Hazardous Components					
Chemical Name	Identifiers	%(weight)	LD50/LC50	Classifications According to Regulation/Directive	Comments
Argon	CAS:7440-37-1	68% TO 96%	NDA	EU DSD/DPD: Not Classified EU CLP: Press. Gas - Comp., H280 OSHA HCS 2012: Press. Gas - Comp.; Simple Asphyx.	Balance
Carbon dioxide	CAS:124-38-9	3% TO 28%	Inhalation-Rat LC50 • 470000 ppm 30 Minute(s)	EU DSD/DPD: Not Classified EU CLP: Annex VI - Press. Gas - Comp., H280 OSHA HCS 2012: Press. Gas - Comp.; Simp. Asphyx.	NDA
Oxygen	CAS:7782-44-7	1% TO 4%	NDA	EU DSD/DPD: Annex I - O; R8 EU CLP: Annex VI - Ox. Gas 1 - H270; Press. Gas - Comp, H280 OSHA HCS 2012: Ox. Gas 1; Press Gas. - Comp.	NDA

See Section 16 for full text of H-statements and R-phrases.

Section 4 - First Aid Measures**4.1 Description of first aid measures****Inhalation**

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Administer oxygen if breathing is difficult. Give artificial respiration if victim

- is not breathing. If signs/symptoms continue, get medical attention.
- Skin**
- Although exposure is unlikely, in case of contact immediately flush skin with running water. If skin irritation develops get medical advice/attention.
- Eye**
- First aid is not expected to be necessary if material is used under ordinary conditions and as recommended. If irritation develops and persists, get medical attention.
- Ingestion**
- Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician

- All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred. A potential health hazard associated with this gas is anoxia.

4.4 Other information

- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. RESCUERS SHOULD NOT ATTEMPT TO RETRIEVE VICTIMS OF EXPOSURE TO GASES WITHOUT ADEQUATE PERSONAL PROTECTIVE EQUIPMENT. At a minimum, Self-Contained Breathing Apparatus must be worn. Victim(s) who experience any adverse effect after over-exposure to this gas mixture must be taken for medical attention. Rescuers should be taken for medical attention if necessary. Take a copy of the label and the MSDS to physician or other health professional with victim(s).

Section 5 - Firefighting Measures

5.1 Extinguishing media

- Suitable Extinguishing Media**
- Use extinguishing agent suitable for type of surrounding fire.
SMALL FIRES: Dry chemical or CO₂.
LARGE FIRES: Water spray or fog.

- Unsuitable Extinguishing Media**
- No data available

5.2 Special hazards arising from the substance or mixture

- Unusual Fire and Explosion Hazards**
- Containers may explode when heated.
Ruptured cylinders may rocket.

- Hazardous Combustion Products**
- None known.

5.3 Advice for firefighters

- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.
Wear positive pressure self-contained breathing apparatus (SCBA).
Move containers from fire area if you can do it without risk.
FIRE: If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.
FIRE INVOLVING TANKS: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
FIRE INVOLVING TANKS: Cool containers with flooding quantities of water until well after fire is out.
FIRE INVOLVING TANKS: Do not direct water at source of leak or safety devices; icing may occur.
FIRE INVOLVING TANKS: Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
FIRE INVOLVING TANKS: ALWAYS stay away from tanks engulfed in fire.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Precautions

- Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material. Ventilate the area before entry.

Emergency Procedures

- Stop leak if you can do it without risk. Keep unauthorized personnel away. Keep out of low areas. Stay upwind. Do not direct water at spill or source of leak. **LARGE SPILL:** Consider initial downwind evacuation for at least 500 meters (1/3 mile)

6.2 Environmental precautions

- No special environmental precautions necessary.

6.3 Methods and material for containment and cleaning up

Containment/Clean-up Measures

- Stop leak if you can do it without risk. Do not direct water at spill or source of leak. Use water spray to reduce vapors; do not put water directly on leak, spill area or inside container. If possible, turn leaking containers so that gas escapes rather than liquid. Isolate area until gas has dispersed. Ventilate the area. Allow substance to evaporate.

6.4 Reference to other sections

- Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Handling

- Use only with adequate ventilation. Ventilate closed spaces before entering. Be aware of any signs of dizziness or fatigue, especially if work is done in a poorly ventilated area; exposures to fatal concentrations of this gas mixture could occur without any significant warning symptoms, due to olfactory fatigue or oxygen deficiency. Cylinders should be firmly secured to prevent falling or being knocked-over. Do not attempt to repair, adjust, or in any other way modify cylinders. If there is a malfunction or another type of operational problem, contact nearest distributor immediately. Empty containers retain product residue and can be hazardous. Do not cut, weld, puncture or incinerate container.

7.2 Conditions for safe storage, including any incompatibilities

Storage

- Store in a cool, dry, well-ventilated place. Protect cylinders against physical damage. Cylinders should be firmly secured to prevent falling or being knocked-over.

7.3 Specific end use(s)

- Refer to Section 1.2 - Relevant identified uses.

Section 8 - Exposure Controls/Personal Protection

8.1 Control parameters

Exposure Limits/Guidelines

	Result	ACGIH	Canada Ontario	Canada Quebec	China	Europe
Carbon dioxide	TWAs	5000 ppm TWA	5000 ppm TWA	5000 ppm TWAEV; 9000 mg/m ³ TWAEV	9000 mg/m ³ TWA	5000 ppm TWA; 9000 mg/m ³ TWA

(124-38-9)	STELs	30000 ppm STEL	30000 ppm STEL	30000 ppm STEV; 54000 mg/m3 STEV	18000 mg/m3 STEL	Not established
Exposure Limits/Guidelines (Con't.)						
	Result	France	Germany DFG	Germany TRGS	Ireland	Israel
Carbon dioxide (124-38-9)	TWAs	5000 ppm TWA [VME] (indicative limit); 9000 mg/m3 TWA [VME] (indicative limit)	Not established	5000 ppm TWA AGW (exposure factor 2); 9100 mg/m3 TWA AGW (exposure factor 2)	5000 ppm TWA; 9000 mg/m3 TWA	5000 ppm TWA
	STELs	Not established	Not established	Not established	Not established	30000 ppm STEL
	Ceilings	Not established	10000 ppm Peak; 18200 mg/m3 Peak	Not established	Not established	Not established
	MAKs	Not established	5000 ppm TWA MAK; 9100 mg/m3 TWA MAK	Not established	Not established	Not established
Exposure Limits/Guidelines (Con't.)						
	Result	Italy	NIOSH	OSHA	Portugal	Spain
Carbon dioxide (124-38-9)	STELs	Not established	30000 ppm STEL; 54000 mg/m3 STEL	Not established	30000 ppm STEL [VLE-CD]	Not established
	TWAs	5000 ppm TWA; 9000 mg/m3 TWA	5000 ppm TWA; 9000 mg/m3 TWA	5000 ppm TWA; 9000 mg/m3 TWA	5000 ppm TWA [VLE- MP]	5000 ppm TWA [VLA- ED] (indicative limit value); 9150 mg/m3 TWA [VLA-ED] (indicative limit value)
Exposure Limits/Guidelines (Con't.)						
	Result	Sweden				
Carbon dioxide (124-38-9)	STELs	10000 ppm STV; 18000 mg/m3 STV				
	TWAs	5000 ppm LLV; 9000 mg/m3 LLV				

Exposure Control Notations

Portugal

- Argon (7440-37-1): **Simple Asphyxiants:** (Simple Asphyxiant)

Canada Ontario

- Argon (7440-37-1): **Simple Asphyxiants:** (Simple asphyxiant)

Canada Quebec

- Argon (7440-37-1): **Simple Asphyxiants:** (Simple asphyxiant)

Ireland

- Argon (7440-37-1): **Simple Asphyxiants:** (Asphyxiant)

Spain

- Argon (7440-37-1): **Simple Asphyxiants:** (simple asphyxiant)

8.2 Exposure controls

Engineering Measures/Controls

- Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal Protective Equipment

Respiratory

- In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face

- Wear safety glasses.

Skin/Body

- Wear leather gloves when handling cylinders.

Environmental Exposure Controls

- Follow best practice for site management and disposal of waste. Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways.

Key to abbreviations

LLV = Limit Level Value is the exposure limit for 8-hour work day
 STEL = Short Term Exposure Limits are based on 15-minute exposures
 TWAEV = Time-Weighted Average Exposure Value
 TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

ACGIH = American Conference of Governmental Industrial Hygiene
 NIOSH = National Institute of Occupational Safety and Health
 OSHA = Occupational Safety and Health Administration

Section 9 - Physical and Chemical Properties**9.1 Information on Physical and Chemical Properties**

Material Description			
Physical Form	Gas	Appearance/Description	Colorless, odorless gas mixture.
Color	Colorless	Odor	Odorless
Odor Threshold	Data lacking		
General Properties			
Boiling Point	-185.9 C(-302.62 F) Argon	Melting Point	-189.2 C(-308.56 F) Argon
Decomposition Temperature	Data lacking	pH	Data lacking
Specific Gravity/Relative Density	Data lacking	Water Solubility	0.056 % @ 0 C(32 F) Argon
Viscosity	Data lacking	Explosive Properties	Not explosive.
Oxidizing Properties:	Not an oxidizer.		
Volatility			
Vapor Pressure	Data lacking	Vapor Density	1.38 Air=1 Argon
Evaporation Rate	Data lacking		
Flammability			
Flash Point	Not relevant	UEL	Not relevant
LEL	Not relevant	Autoignition	Not relevant
Flammability (solid, gas)	Not flammable.		
Environmental			
Octanol/Water Partition coefficient	Data lacking		

9.2 Other Information

- No additional physical and chemical parameters noted.

Section 10: Stability and Reactivity**10.1 Reactivity**

- No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

- Stable under normal temperatures and pressures.

10.3 Possibility of hazardous reactions

- Hazardous polymerization will not occur.

10.4 Conditions to avoid

- Avoid exposing cylinders to extremely high temperatures, which could cause cylinders to rupture.

10.5 Incompatible materials

- Carbon dioxide, being weakly acidic, reacts with alkaline materials to form carbonates and bicarbonates. Reacts with organic and reducing materials. Carbon Dioxide, a component of this gas mixture, will ignite and explode when heated with powdered aluminum, beryllium, cerium alloys, chromium, magnesium-aluminum alloys, manganese, thorium, titanium, and zirconium. In the presence of moisture, Carbon Dioxide will ignite with cesium oxide. Metal acetylides will also ignite and explode on contact with Carbon Dioxide.

10.6 Hazardous decomposition products

- None

Section 11 - Toxicological Information

11.1 Information on toxicological effects

Component Name	CAS	Data
Carbon dioxide (3% TO 28%)	124-38-9	Acute Toxicity: ihl-rat LC50:470000 ppm/30M; Reproductive: ihl-rat TCLo:6 pph/24H (10D preg)
Oxygen (1% TO 4%)	7782-44-7	Reproductive: ihl-rat TCLo:10 pph/9H (22D preg)

GHS Properties	Classification
Acute toxicity	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Aspiration Hazard	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Carcinogenicity	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Germ Cell Mutagenicity	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Skin corrosion/Irritation	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Skin sensitization	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
STOT-RE	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
STOT-SE	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Toxicity for Reproduction	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Respiratory sensitization	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Serious eye damage/Irritation	EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met

Route(s) of entry/exposure

- Inhalation, Skin, Eye, Ingestion

Potential Health Effects

Inhalation

Acute (Immediate)

- Can increase respiration and heart rate. If this material is released in a small, poorly ventilated area (i.e. an enclosed or confined space), an oxygen-deficient environment may occur. Individuals breathing such an atmosphere may experience symptoms which include headaches, ringing in ears, dizziness, drowsiness, unconsciousness, nausea, vomiting, and depression of all the senses. Under some circumstances of over-exposure, death may occur. The following effects associated with decreased levels of oxygen: increase in breathing and pulse rate, emotional upset, abnormal fatigue, nausea, vomiting, collapse, loss of consciousness, convulsive movements, respiratory collapse and death.

Chronic (Delayed)

- No data available

Skin

Acute (Immediate)

- Under normal conditions of use, no health effects are expected.

Chronic (Delayed)

- Under normal conditions of use, no health effects are expected.

Eye

Acute (Immediate)

- Under normal conditions of use, no health effects are expected.

Chronic (Delayed)

- Under normal conditions of use, no health effects are expected.

Ingestion

Acute (Immediate)

- Ingestion is not anticipated to be a likely route of exposure to this product.

Chronic (Delayed)

- Ingestion is not anticipated to be a likely route of exposure to this product.

Mutagenic Effects

- No data available.

Carcinogenic Effects

- The components of this material are not found on the following lists: FEDERAL OSHA Z LIST, NTP and IARC; therefore, they are not considered to be, nor suspected to be, cancer-causing agents by these agencies.

Reproductive Effects

- No data available.

Section 12 - Ecological Information

12.1 Toxicity

- Material data lacking.

12.2 Persistence and degradability

- Material data lacking.

12.3 Bioaccumulative potential

- Material data lacking.

12.4 Mobility in Soil

- Material data lacking.

12.5 Results of PBT and vPvB assessment

- PBT and vPvB assessment has not been conducted for this material.

12.6 Other adverse effects

- Material data lacking.

Section 13 - Disposal Considerations

13.1 Waste treatment methods

Product waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	UN1956	Compressed gas, n.o.s. (Argon, Carbon Dioxide)	2.2	NDA	NDA
TDG	UN1956	COMPRESSED GAS, N.O.S. (Argon, Carbon Dioxide)	2.2	NDA	NDA
IMO/IMDG	UN1956	COMPRESSED GAS, N.O.S. (Argon, Carbon Dioxide)	2.2	NDA	NDA
IATA/ICAO	UN1956	Compressed gas, n.o.s. (Argon, Carbon Dioxide)	2.2	NDA	NDA

14.6 Special precautions for user

- Cylinders should be transported in a secure position, in a well-ventilated vehicle. The transportation of compressed gas cylinders in automobiles or in closed-body vehicles can present serious safety hazards. If transporting these cylinders in vehicles, ensure these cylinders are not exposed to extremely high temperatures (as may occur in an enclosed vehicle on a hot day). Additionally, the vehicle should be well-ventilated during transportation.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

- Not relevant.

Section 15 - Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications

- Acute, Pressure(Sudden Release of)

State Right To Know				
Component	CAS	MA	NJ	PA
Argon	7440-37-1	Yes	Yes	Yes
Carbon dioxide	124-38-9	Yes	Yes	Yes
Oxygen	7782-44-7	Yes	Yes	Yes

Inventory						
Component	CAS	Canada DSL	Canada NDSL	China	EU EINECS	EU ELNICS
Argon	7440-37-1	Yes	No	Yes	Yes	No
Carbon dioxide	124-38-9	Yes	No	Yes	Yes	No

Oxygen	7782-44-7	Yes	No	Yes	Yes	No
Inventory (Con't.)						
Component	CAS	Japan ENCS	Korea KECL	TSCA		
Argon	7440-37-1	No	Yes	Yes		
Carbon dioxide	124-38-9	Yes	Yes	Yes		
Oxygen	7782-44-7	No	Yes	Yes		

Canada

Labor

Canada - WHMIS - Classifications of Substances

- Oxygen 7782-44-7 1% TO 4% A, C
- Carbon dioxide 124-38-9 3% TO 28% A; Uncontrolled product according to WHMIS classification criteria (solid)
- Argon 7440-37-1 68% TO 96% A

Canada - WHMIS - Ingredient Disclosure List

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% 1 %
- Argon 7440-37-1 68% TO 96% Not Listed

Environment

Canada - CEPA - Priority Substances List

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

China

Environment

China - Ozone Depleting Substances - First Schedule

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

China - Ozone Depleting Substances - Second Schedule

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

China - Ozone Depleting Substances - Third Schedule

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

Other

China - Annex I & II - Controlled Chemicals Lists

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

China - Dangerous Goods List

- Oxygen 7782-44-7 1% TO 4% UN1072; UN1073
- Carbon dioxide 124-38-9 3% TO 28% UN1013; UN1845 PG = III; UN2187
- Argon 7440-37-1 68% TO 96% UN1006; UN1951

China - Export Control List - Part I Chemicals

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

Europe

Other

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Classification

- Oxygen 7782-44-7 1% TO 4% O; R8
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Concentration Limits

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Labelling

- Oxygen 7782-44-7 1% TO 4% O R:8 S:(2)-17
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Notes - Substances and Preparations

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Safety Phrases

- Oxygen 7782-44-7 1% TO 4% S:(2)-17
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

Germany

Environment

Germany - TA Luft - Types and Classes

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

Germany - Water Classification (VwVwS) - Annex 1

- Oxygen 7782-44-7 1% TO 4% ID Number 743, not considered hazardous to water
- Carbon dioxide 124-38-9 3% TO 28% ID Number 256, not considered hazardous to water
- Argon 7440-37-1 68% TO 96% ID Number 1348, not considered hazardous to water

Germany - Water Classification (VwVwS) - Annex 2 - Water Hazard Classes

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

Germany - Water Classification (VwVwS) - Annex 3

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

Other

Germany - Specifically Regulated Chemicals in TRGS

- Oxygen 7782-44-7 1% TO 4% Not Listed

- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

Mexico

Other

Mexico - Hazard Classifications

- Oxygen 7782-44-7 1% TO 4% Hazard Class = 2.2 (5.1) UN1072; Hazard Class = 2.2 (5.1) UN1073
- Carbon dioxide 124-38-9 3% TO 28% Hazard Class = 2.2 UN1013; Hazard Class = 9 PG = III UN1845; Hazard Class = 2.3 UN2187
- Argon 7440-37-1 68% TO 96% Hazard Class = 2.2 UN1006; Hazard Class = 2.2 UN1951

Mexico - Regulated Substances

- Oxygen 7782-44-7 1% TO 4% UN1072; UN1073
- Carbon dioxide 124-38-9 3% TO 28% UN1013; UN1845; UN2187
- Argon 7440-37-1 68% TO 96% UN1006; UN1951

Portugal

Other

Portugal - Prohibited Substances

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

United Kingdom

Environment

United Kingdom - Pollution Inventory - Schedule 1 - Thresholds for Releases to Air

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% 10000000 kg (qualifying renewable fuel sources are reportable when the total amount of CO2 released is above 10 million kg); 10000000 kg
- Argon 7440-37-1 68% TO 96% Not Listed

United Kingdom - Substances Contained in Dangerous Substances or Preparations

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

Other

United Kingdom - Workplace Exposure Limits (WELs) - Substances in Review

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

United Kingdom - The Red List - Dangerous Substances in Water

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

United States

Labor

U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

U.S. - OSHA - Specifically Regulated Chemicals

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

Environment

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

U.S. - California - Proposition 65 - Developmental Toxicity

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed

- Argon 7440-37-1 68% TO 96% Not Listed

U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

U.S. - California - Proposition 65 - Reproductive Toxicity - Female

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

U.S. - California - Proposition 65 - Reproductive Toxicity - Male

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

United States - Pennsylvania

Labor

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances

- Oxygen 7782-44-7 1% TO 4% Not Listed
- Carbon dioxide 124-38-9 3% TO 28% Not Listed
- Argon 7440-37-1 68% TO 96% Not Listed

15.2 Chemical Safety Assessment

- No Chemical Safety Assessment has been carried out.

Section 16 - Other Information

Relevant Phrases (code & full text)

- H270 - May cause or intensify fire; oxidizer
- R8 - Contact with combustible material may cause fire.

Last Revision Date

- 28/May/2013

Preparation Date

- 28/May/2013

Disclaimer/Statement of Liability

- To the best of Air Liquide's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this gas mixture is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

Key to abbreviations

NDA = No Data Available
